First responder thermal imaging cameras: representative testing conditions & performance metrics



Francine Amon, Anthony Hamins, Nelson Bryner, Sung Chan Kim, Gwon Hyun Ko, Paul Boynton, Joshua Dinaburg, Justin Rowe, Andrew Lock

Fire Research Division
Building and Fire Research Laboratory



### **Overall Research Objectives**

- Assess the thermal imaging activities and needs of first responders.
- Establish a range of testing conditions that simulate the operating environment.
- Determine the extent to which the camera display effects the performance of the camera.
- Evaluate the effects of human perception.
- Identify appropriate imaging performance metrics and develop standard performance testing methods.




### **Approach**

- User Input: TIC operations
  - Workshop on Thermal Imaging Needs for First Responders
- Existing standards/ Relevant work by others
  - Thermal classes
  - Literature sources
- Full-scale tests/ Bench-scale tests
- Propose TIC testing conditions
- Develop image quality performance metrics
- Recommend standard test methods



# **TIC Operations- A Sampling**



Locate fire sources



**Overhaul** 




Navigation in smoke/dark






### Consolidation

	<u>Class I</u>	<u>Class II</u>	Class III
<u>Class</u>	water, fog, or snow possible, minimal heat, smoke and flames	elevated temperatures, water, dust, smoke and flames may be present	high temperatures and smoke concentrations, flames, dust, and water are likely
<u>Activity</u>	Hazmat Medical Motor vehicle accident Search	Overhaul Size up Tactics Forensics Preventative maintenance Search	Forensics Wildland fires Size up Tactics Communication Search
Proposed Tests	Contrast Obscurants Spatial Resolution Thermal Sensitivity Uniformity	Contrast Obscurants Effective Temperature Range Spatial Resolution Thermal Sensitivity Uniformity	Contrast Obscurants Spatial Resolution Thermal Sensitivity Uniformity 5



# Full-Scale Tests (I)











### Full-Scale Tests (II)








- Imagers in upper and lower layer
- Targets: exit signs, mannequins, controlled temperature target
- Soot, dust, steam, water, varying fuels


#### **Performance Metrics**

- Contrast & Effective Temperature Range
  - Determine the point at which the displayed image loses its usefulness
- Electro-Optical Transfer Function (EOTF)
  - Relationship between displayed image and captured video output
- Obscurant Effects
- Spatial Resolution
  - Not directly dependent on thermal target
  - Use random MTF target?
- Thermal Sensitivity
  - Perceivable thermal sensitivity, viewing targets in various thermal classes
  - Camera itself exposed to elevated temperatures
- Uniformity of Display




#### **Contrast Transfer Function**






### Contrast & Effect Temp Range




### **Electro-Optical Transfer Function**







# **Spatial Resolution**



### **Thermal Sensitivity**







Potential targets include electrical outlets, light ballasts, vents, windows, and people.







**Infrared** 



#### Collaborations & Future Work

- NIST Physics Lab
  - Hyperspectral projector
- NIST Electronics and Electrical Lab
  - Display measurements
- Night Vision Lab
  - Test human perception of displayed thermal images
- OLES
  - Field calibration target
  - Non-fire environments
- University of Central Florida
  - Random MTF target development
- Standards committees: ASTM, NFPA, FSTICWG
- Simulated obscurants for bench-scale tests

# **Acknowledgments**

- Funds for this project have been provided by the Department of Homeland Security (DHS), the United States Fire Administration (USFA), the Office of Law Enforcement Standards (OLES), NIST (AFST), and NIST (ATP).
- NIST staff: Marc Nyden, Yong Shik Han, Roy McLane, Jay McElroy.
- The assistance of the capable crew at the NIST Large Fire Facility is very much appreciated.
- Gerald C. Holst